

TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD
ZERTIFIKAT ♦ CERTIFICATE ♦ 認證證書 ♦ CERTIFICADO ♦ CERTIFIKAT ♦ CERTIFICAT



Product Service

CERTIFICATE

No. Z2 021662 0320 Rev. 00

Holder of Certificate: **Kompan Design Studio & Manufacturing,
Berlin GmbH**
Holzhauser Str. 139
13509 Berlin
GERMANY

Certification Mark:



Product: **Playground equipment**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

Test report no.: 713150160-11

Valid until: 2024-03-20

Date, 2019-08-30

(Jens Bieshack)



Product Service

CERTIFICATE

No. Z2 021662 0320 Rev. 00

Model(s):

COROCORD™

**COR 6214, COR 6226, COR 6300, COR 6330
COR 6412, COR 6500, COR 6612, COR 6690,
COR 6691, COR 6692, COR 6700, COR 6804,
COR 6806**

Parameters:

Rope net bridges made of Corocord rope with a Ø of 19-23 mm.

Support posts made of hot-galvanised steel, alternatively splinter-free wooden posts (applies to models 6300, 6330, 6612 and 6700).

The following parts can be found with the models: steel-reinforced rubber belt, net, coconut rope, PP rope, wooden flooring or stainless steel slide.

COR 6214:

L/W/H: 14.00/ 3.60/ 4.10 m

Max. falling height: 1.00 m

COR 6226:

L/W/H: 26.00/ 3.60/ 6.00 m

Max. falling height: 2.00 m

COR 6300:

L/W/H: 12.00/ 1.03/ 2.90 m

Max. falling height: 2.25 m

COR 6330:

L/W/H: 10.00/ 1.20/ 1.38 m

Max. falling height: 3.00 m

COR 6412:

L/W/H: 12.00/ 1.25/ 2.65 m

Max. falling height: 1.85 m

COR 6500:

L/W/H: 9.00/ 1.20/ 2.75 m

Max. falling height: 2.75 m

COR 6612:

L/W/H: 12.00 m / 0.90 m / 2.90 m

Max. falling height: 2.05 m

COR 6690:

L/W/H: 5.80/ 1.35/ 2.30 m

Max. falling height: 1.50 m

COR 6691:

L/W/H: 6.50/ 1.35/ 2.80 m

Max. falling height: 2.00 m

TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD
ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ СЕРТИФИКАТ ◆ CERTIFICADO ◆ CERTIFICAT



Product Service

CERTIFICATE

No. Z2 021662 0320 Rev. 00

COR 6692:	
L/W/H:	7.05/ 1.35/ 3.20 m
Max. falling height:	2.40 m
COR 6700:	
L/W/H:	12.00/ 1.50/ 3.50 m
Max. falling height:	2.55 m
COR 6804:	
L/W/H:	4.00/ 0.80/ 0.90 m
Max. falling height:	1.10 m
COR 6806:	
L/W/H:	6.00/ 0.80/ 1.90 m
Max. falling height:	1.10 m

**Tested
according to:**

DIN EN 1176-1:2017
DIN EN 1176-3:2017
EN 1176-1:2017
EN 1176-3:2017

**Production
Facility(ies):**

021662