



Product Service

CERTIFICATE

No. Z2 021662 0322 Rev. 00

Model(s):

COROCORD™

COR 4140, COR 4142, COR 41422, COR 41424,
COR 4240, COR 42402, COR 42432, COR 4340,
COR 4348

Parameters:

Space nets with truncated octahedron rope cells with centre mast and side supports as 1-2-3-4 masters, designed with mesh widths of 40-48 cm.

The equipment consists of Corocord rope with a diameter of 19-24 mm and 7.5 mm thick membranes made of polyester fabric with rubber coating.

COR 4140 Star octa net

L/W/H: 3.98/4.16/2.80 m

Max. falling height: 2.80 m

COR 4142 Octa net S

L/W/H: 6.81/6.81/3.85 m

Max. falling height: 1.50 m

COR 41422 Small two-mast octa net

L/W/H: 6.81/ 10.80/ 3.85 m

Max. falling height: 1.50 m

COR 41424 Small four-mast octa net

L/W/H: 11.60/11.60/3.85 m

Max. falling height: 1.50 m

COR 4240 Octa net M

L/W/H: 9.20/9.20/6.00 m

Max. falling height: 2.25 m

COR 42402 Large two-mast octa net

L/W/H: 17.70/11.20/6.00 m

Max. falling height: 2.25 m

COR 42432 Giant two-mast octa net

L/W/H: 22.92/15.32/8.70 m

Max. falling height: 2.80 m

COR 4340 Octa net L

L/W/H: 13.00/13.00/8.70 m

Max. falling height: 2.60 m

COR 4348 Octa net XL

L/W/H: 15.34/15.34/10.45 m

Max. falling height: 3.00 m

TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD
ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFICAT

